



DIRECTIONALS



3750 SERIES R65 Compact Directional LED

The 3750 series is a high intensity R65 approved directional LED warning light specifically designed for compact use. It can also be surface, collar and L bracket mounted to the vehicle exterior using the included mounting bezel. Featuring four LEDs that provide exceptional warning. A sealed in-line driver module eliminates the need for a remote power supply. This product series also features multiple flash patterns and synchronisation capability.

Models

PART NO.	VOLTAGE	AMPS	FLASH PATTERNS	MOUNT
3750X	10-30	1.5	21	Surface, Collar, L Bracket

Replace X in part number with desired LED colour: A = amber, B = blue, C = clear, R = red


Features and Benefits

- Four high intensity LEDs provide exceptional warning
- Head/tail light or surface mountable using included bezel
- Multiple head are synchronisable (simultaneous or alternating operation)
- Colourless when not illuminated
- 21 flash patterns
- Operation temp: -30°C to +50°C

Mounting images



Dimensions



In order to meet R65 compliance, must be installed vertically straight up and down

Flash Patterns

Sync Patterns

- Single Flash 75FPM
- Single Flash 75FPM
- Single Flash 120FPM *
- Single Flash 120FPM *
- Double Flash 75FPM
- Double Flash 75FPM
- Double Flash 120FPM*
- Double Flash 120FPM*
- Quad Flash 75FPM
- Quad Flash 75FPM
- Quad Flash 150FPM
- Quad Flash 150FPM
- Triple Alter 75FPM
- Triple Alter 75FPM
- Quint Flash 150FPM
- Quint Flash 150FPM

Non-Sync Patterns

- Steady Burn.
- Module Flash
- Two Double Flash with Triple Flash
- Four Single Flash with Two Quad Flash
- Off

* R65 flash patterns