



DIRECTIONALS



3812 SERIES Surface Mount

3812 Series directional LEDs feature 20 high intensity LEDs with individual reflectors to provide truly outstanding light output in a very cost-effective package. Featuring fifteen flash patterns and synchronisation capability, offering fit-and-forget maintenance-free operation and low amp draw.

Models


PART NO.	VOLTAGE	AMPS	MOUNT
3812X	12-48	0.4	Surface

Replace X in part number with desired color: A=amber, B=blue, C=clear, R=red

Features and Benefits

- Tough, clear polycarbonate housing with encapsulated electronics
- Fifteen flash patterns (seven with phase 1 & 2 + steady burn)
- Synchronisable with additional units
- Discrete units are colourless when not illuminated
- ECE R65 (Amber & Blue)
- ECE R10-05 (EMC)
- Temperature Range: -30°C to +50°C

Dimensions



Flash Patterns (7)

1	ECE R65 DOUBLE FLASH (DEFAULT)	
2	ECE R65 DOUBLE FLASH	PHASE 2
3	ECE R65 SINGLE FLASH	PHASE 1
4	ECE R65 SINGLE FLASH	PHASE 2
5	ECE R65 QUAD FLASH	PHASE 1
6	ECE R65 QUAD FLASH	PHASE 2
7	STEADY BURN	
8	TRIPLE FLASH (75FPM)	PHASE 1
9	TRIPLE FLASH (75FPM)	PHASE 2
10	SINGLE FLASH (75FPM)	PHASE 1
11	SINGLE FLASH (75FPM)	PHASE 2
12	DOUBLE FLASH (75FPM)	PHASE 1
13	DOUBLE FLASH (75FPM)	PHASE 2
14	QUAD FLASH (75FPM)	PHASE 1
15	QUAD FLASH (75FPM)	PHASE 2
16	OFF	