



BEACONS



400 Series R65 LED Beacons

The 400 Series LED Beacons utilise the latest LED technology and features 12 powerful LED's arranged to produce a 360° flash pattern, with a flash rate of 125FPM for maximum visibility. Suitable for applications where the UK lighting regulation Chapter 8 is a requirement. Combining the solid state, maintenance free and long life nature of LED technology with a proven tough housing design. This ECCO, UK produced beacon is designed to maximise resilience to vibration and increase the life of the product.

Models

PART NO.	VOLTAGE	FPM	MOUNT
V11050*	10-30V	125	3 Bolt
V11051*	10-30V	125	1 Bolt Conical
V11052*	10-30V	125	1 Bolt
V11053	10-30V	125	Mag 50
V11054	10-30V	125	Mag 70
V11055	10-30V	125	Flexi DIN Pole
V11056	10-30V	125	DIN Pole
V11057*	10-30V	125	1 Bolt Flexi

Flash Patterns

0 - Steady burn 10% duty cycle (1s sync)	N/A	8 - 75 FPM Triple Flash	B
1 - 60 FPM Single Flash (400ms on)	A	9 - 75 FPM Quad Flash	A
2 - 60 FPM Single Flash (400ms on)	B	10 - 75 FPM Quad Flash	B
3 - 125 FPM single Flash (190ms on) R65	A	11 - 125 FPM Fast Double Flash R65	A
4 - 125 FPM Single Flash (190ms on) R65	B	12 - 125 FPM Fast Double Flash R65	B
5 - 75 FPM Double Flash	A	13 - 60 FPM Static Flash (Airport)	A
6 - 75 FPM Double Flash	B	14 - 60 FPM Static Flash (Airport)	B
7 - 75 FPM Triple Flash	A	15 - Off	N/A

Note:- Patterns 3,4,11 & 12 are ECE R65 Approved. Pattern 11 will be set as default. A & B = Phase.

Dimensions

