



# BEACONS



## 400 Series R65 LED Beacons

The 400 Series LED Beacons utilise the latest LED technology and features 12 powerful LED's arranged to produce a 360° flash pattern, with a flash rate of 125FPM for maximum visibility. Suitable for applications where the UK lighting regulation Chapter 8 is a requirement. Combining the solid state, maintenance free and long life nature of LED technology with a proven tough housing design. This ECCO, UK produced beacon is designed to maximise resilience to vibration and increase the life of the product.

### Models

| PART NO. | VOLTAGE | FPM | MOUNT          |
|----------|---------|-----|----------------|
| V11050*  | 10-30V  | 125 | 3 Bolt         |
| V11051*  | 10-30V  | 125 | 1 Bolt Conical |
| V11052*  | 10-30V  | 125 | 1 Bolt         |
| V11053   | 10-30V  | 125 | Mag 50         |
| V11054   | 10-30V  | 125 | Mag 70         |
| V11055   | 10-30V  | 125 | Flexi DIN Pole |
| V11056   | 10-30V  | 125 | DIN Pole       |
| V11057*  | 10-30V  | 125 | 1 Bolt Flexi   |

### Flash Patterns

|  |     |                                    |     |
|--|-----|------------------------------------|-----|
| 0 - Steady burn 10% duty cycle (1s sync) | N/A | 8 - 75 FPM Triple Flash            | B   |
| 1 - 60 FPM Single Flash (400ms on)       | A   | 9 - 75 FPM Quad Flash              | A   |
| 2 - 60 FPM Single Flash (400ms on)       | B   | 10 - 75 FPM Quad Flash             | B   |
| 3 - 125 FPM single Flash (190ms on) R65  | A   | 11 - 125 FPM Fast Double Flash R65 | A   |
| 4 - 125 FPM Single Flash (190ms on) R65  | B   | 12 - 125 FPM Fast Double Flash R65 | B   |
| 5 - 75 FPM Double Flash                  | A   | 13 - 60 FPM Static Flash (Airport) | A   |
| 6 - 75 FPM Double Flash                  | B   | 14 - 60 FPM Static Flash (Airport) | B   |
| 7 - 75 FPM Triple Flash                  | A   | 15 - Off                           | N/A |

Note:- Patterns 3,4,11 & 12 are ECE R65 Approved. Pattern 11 will be set as default. A & B = Phase.

### Dimensions

