


NOTES:  
1. DIMENSIONS IN MILLIMETRES [INCHES (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION  
THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2018 ELECTRONIC CONTROLS COMPANY

SCALE 1:2			APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: A			DRAWN BY JUP	2019-02-22
			CHECKED LSH	2019-02-22
			MECH. ENG. FP	2019-01-29
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			ELEC. ENG. MMG	2019-02-15
MILLIMETERS DECIMALS XX.X ± 1.0mm XX.XX ± 0.5mm	INCHES DECIMALS X.XX ± 0.1 X.XXX ± 0.04 X.XXXX ± 0.02	ANGLES ± 0.5°  FRACTIONS ± 1/64	TEST ENG. GDH	2019-02-22
THIRD ANGLE PROJECTION 			SALES.	
			Electronically Controlled Use Latest Copy	

		<b>ECCO</b> <sup>®</sup>		<a href="http://www.eccolink.com">www.eccolink.com</a>	
Americas (800) 635-5900		Europe +44 (0)113 237 5340		Asia Pacific +61 (0)3 63322444	
<b>SECURILE, DIRECTIONAL, SURFACE MOUNT</b>					
CUSTOMER PART NO. <b>ED5110X</b>				PRODUCT SERIES: <b>5110</b>	
SIZE: <b>A4</b>		DWG. NO. <b>ED5110X</b>			REV. <b>A</b>
SHEET 1 OF 1		Project: V14024		Date Created: 2018-07-25	

REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER V14024	2018-07-25
02	REVISED PER V14024	2019-01-17
A	INITIAL RELEASE PER V14024	2019-03-20

## SPECIFICATIONS

### 1. CERTIFICATIONS: R10 & R65; SEE CHART

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- FLASH MODE: DOUBLE FLASH: 123 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12 to 24 VDC
- VOLTAGE (EXTREME): 9 to 32 VDC
- CURRENT (PEAK): SEE CHART (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -30°C (-22°F) TO 55°C (131°F)
- CONNECTION: 4-22 AWG WIRES
- MOUNTING: 4 BOLT FIXING
- BEZEL MATERIAL: POLYCARBONATE
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 0.3Kg (0.66 LBS)