

REVISION HISTORY		
REV.	DESCRIPTION	DATE
02	REVISED PER LM14207	2014-09-16
03	REVISED PER LM14207	2014-09-22
Α	INITIAL RELEASE PER LM14207	2014-10-29




- 15' [4572] CORD W/SINGLE SWITCH LIGHTER ADAPTER

SPECIFICATIONS

1. CERTIFICATIONS: **C€**;

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. RAW LUMENS: 1300 lumens
- 3. EFFECTIVE LUMENS: 1100 lumens
- 4. ILLUMINANCE: lux
- 5. PEAK BEAM INTENSITY: Candela
- 6. EFFICACY: 43.4 lm/W
- 7. CORRELATED COLOR TEMPERATURE: 6922K
- 8. VOLTAGE (NOMINAL): 12 to 36 VDC
- 9. VOLTAGE (EXTREME): 10.0 to 40.0 VDC
- 10. CURRENT (PEAK): 2.2A (@ 12 VDC NOMINAL)
- 11. POWER (MAXIMUM): 30.8W (@ 12 VDC NOMINAL)
- 12. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 13. CONNECTION: 2-18 AWG WIRES W/LIGHTER ADAPTER
- 14. MOUNTING: MAGNET MOUNT
- 15. HOUSING MATERIAL: ALUMINUM
- 16. LENS MATERIAL: POLYCARBONATE
- 17. PRODUCT WEIGHT: 2.6 LBS (1.17 Kg)



NOTES: 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONDIDENCE FOR ENGINEERING INFORMATION. ONLY, THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPPIED, REPRODUCED, OR O'NIERWISE DISCLOSED IN PART OR, AS A WHOLE TO OUTSIDERS COUSED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DECIMENT AND THE PRIVATE AND THE PRIVAT





Electronic Controls Co.

833 West Diamond Street, Boise,ID 83705

800-635-5900 www.eccolink.com

WORKLAMP,9LED,SQUARE,FLOOD,12-24V,MG

 TEST ENG.
 JRT
 2014-10-22
 CUSTOMER PART NO. EW2451 - MG
 PRODUCT SERIES: EW2451

 SALES.
 LAT
 2014-09-22
 SIZE: A DWG. NO. EW2451 - MG

Electronically Controlled Use Latest Copy | SHEET 1 OF 1 | Project: LM14207 | Date Created: 2014-09-11

