

REVISION HISTORY									
REV.	DESCRIPTION	DATE							
D	REVISE PER VA CR 1641	2014-03-04							
Е	REVISE PER VA CR 1641	2015-06-15							
F	REVISED PER LC3039	2020-12-17							

## **SPECIFICATIONS**

1. CERTIFICATIONS: ECE R10: R65 & IP65:


Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test protocols. Unless otherwise specified, the product certifications referred to herein are predicated upon the base product model configuration.

Date Created: 09-Jun-04

- 2. FLASH MODE: 125 FPM DOUBLE FLASH
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. VOLTAGE (EXTREME): 10 to 30 VDC
- 5. CURRENT (AVG): 1.2A (@ 12 VDC NOMINAL)
- 6. CURRENT (PEAK): 2A (@ 12VDC NOMINAL)
- 7. POWER (RMS MAXIMUM): 24W (@ 12 VDC NOMINAL)
- 8. TEMPERATURE RANGE: -30°C (-4°F) TO 50°C (122°F)
- 9. CONNECTION: 18 AWG WIRES
- 10. MOUNTING: 3 BOLT MOUNTING
- 11. BASE MATERIAL: POLYCARBONATE
- 12. LENS MATERIAL: POLYCARBONATE
- 13. PRODUCT WEIGHT: 0.6 Kg (1.32 LBS)

							,				
	SCALE 1:3			API	PROVALS	DATE					
	DO NOT MANUALLY UPDATE. MODEL REFERENCED: D			DRAWN BY	CRT	2020-12-02		ECC	www.eccol	link.com	
				CHECKED	LSH	2020-12-01	<b></b>				
				MECH. ENG.	KW	2020-12-07	(,	Americas (800) 635-5900   Europe +44 (0)113 237 5340   Asia Pacific +61 (0)3 63322444			
Ī	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	MMG	2020-12-03	BEACO	N, 400 SER	IES, 3 BOLT, AMB, L	ED R65	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	AD	2020-12-16	CUSTOMER PAR				
			± 1/64	SALES.			V11030	- V11050			
TES	THIRD ANGLE PROJECTION						SIZE: A4	DWG. NO.	V11050	REV.	

Electronically Controlled Use Latest Copy | SHEET 1 OF 1 | Project: 12002



## NOTES:

- 1. DIMENSIONS IN MILLIMETERS [INCHES (FOR REFERENCE)]
- 2. USE SUB ASSEMBLY (100-V11050) FOR MANUFACTURE